

MATERIAL SAFETY DATA SHEET

Company Name: Superior Stone Products, Inc.
Product Name: Superior Acry-Tyte (Various Colors)
 Issue Date: 5/16/08
 Revision Date: 12/3/08
 MSDS Number: SUP-15500



Section I – Chemical Product and Company Identification

Product Identifier: Superior Acry-Tyte (Various Colors)

This MSDS covers the following Superior Acry-Tyte Colors

Almond	Amarillo	Aquamarine	Arctic White	Aztec	Bamboo	Battleship Gray
Black	Black Anubis	Black Night	Brick	Butterscotch	Camelback	Candell
Caribou	Celadon	Champagne	Charcoal	Clear	Cobalt	Cotton
Dandelion	Desert Gold	Eclipse	Espresso	Fire Engine Red	Goldenrod	Graphite Gray
Gunmetal	Honey	Honeycomb	Ivory	Java	Khaki	Macadamia
Mahogany	Midnight Blue	Midnight Green	Mocha Gray	Neutral	Olive	Oyster Shell
Pearl	Pewter	Polar White	Portabella	Robins Egg	Rococco	Rustic Gold
Sable	Saffron	Sage	Sand Dune	Santa Fe	Shingle	Silver Sky
Smoke Gray	Starlite Gray	Starlite White	Stucco	Tan	Taupe	Tortoise
Tumbleweed	Vanilla	Wrought Iron				

Product Description: Part 1 - Acrylic / Part 2 - Organic Peroxide

Manufacturer:

Superior Stone Products, Inc.
 8580 Byron Commerce Drive
 Byron Center, MI 49315
 616-583-0171

24 Hour Emergency Telephone Number:
CHEMTREC 800-424-9300

Section II – Composition/Information on Ingredients

If present, IARC, NTP and OSHA carcinogens and chemicals subject to the reporting requirements of SARA title III Section 313 are identified in this Section.

Part 1

<u>Ingredient</u>	<u>CAS#</u>	<u>% (By Weight)</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Methyl Methacrylate	80-62-6	55-75%	100 PPM	50 PPM
Poly (Methyl Methacrylate Ethyl Methacrylate)	9010-88-2	10-30%	Not Established	Not Established
Triethylene Glycol Dimethacrylate Esters	109-16-0	1-15%	Not Established	Not Established
Amorphus Fumed Silica	112945-52-5	<10%	5 mg/m ³ (Respirable)* 15 mg/m ³ (Total)*	5 mg/m ³ (Respirable)* 15 mg/m ³ (Total)*

* Particulates Not Otherwise Regulated

Part 2

<u>Ingredient</u>	<u>CAS#</u>	<u>% (By Weight)</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Benzoyl Peroxide	94-36-0	<15%	5 mg/m ³	5 mg/m ³
Bisphenol A/Epichlorohydrin Based Epoxy Resin	25068-38-6	<70%	Not Established	Not Established

MATERIAL SAFETY DATA SHEET

Company Name: Superior Stone Products, Inc.
Product Name: Superior Acry-Tyte (Various Colors)
Issue Date: 5/16/08
Revision Date: 12/3/08
MSDS Number: SUP-15500

Section III – Hazards Identification/Possible Routes of Entry

Caution: Part 1 - Flammable Liquid Part 2 - Organic Peroxide

Ingestion: May cause irritation, a burning sensation of the mouth throat and gastrointestinal tract and abdominal pain.

Skin: May cause skin irritation, skin sensitization or defatting. May be readily absorbed through the skin.

Eye: May cause eye irritation. May cause lachrymation (tears), blurred vision and redness.

Inhalation: High concentration is irritant to the respiratory tract and may cause dizziness, headache and anesthetic effects and/or nausea. Aspiration of material into lungs may result in chemical pneumonitis which may be fatal.

HMIS Codes:

Flammability:	3
Health:	2
Physical Hazard:	2
Personal Protective Index:	X

Section IV – First Aid Measures

If Swallowed: Do not induce vomiting unless directed by a medical professional. Give victim 2 glasses of water if conscious. Never give anything by mouth to an unconscious person. Prevent aspiration of vomit. Turn victims head to the side. Seek immediate medical attention.

Skin Contact: Remove contaminated clothing. Immediately wash area with soap and water. Continue irrigating skin until medical assistance is obtained. Seek immediate medical attention if irritation develops or persists.

If Inhaled: Remove to fresh air. If breathing is labored or has stopped artificial respiration may be provided by a certified individual at the direction of a medical professional. Seek immediate medical attention.

Eyes: Hold eyelids apart and immediately flush with water for at least 15 minutes. Seek immediate medical attention. If medical attention is not immediately available continue irrigation until patient receives medical care.

Section V - Fire Fighting Measures

Part 1

Flash Point: 11.5°C (52.7°F) (Estimated)
Class IB Flammable Liquid

Part 2

Flash Point: >84°C (>184°F) (Estimated)
May be Combustible when dry

Hazardous Products of Combustion: Acrid smoke/fumes/carbon monoxide and other toxic vapors may be generated during combustion. Do not allow runoff from fire fighting to enter drains or water courses.

Extinguishing Agents: Use water fog, foam, dry chemical, dry sand, limestone powder or carbon dioxide. Water spray may be used to cool down tanks in proximity to the fire.

Special Fire Fighting Procedures: Utilize full protective clothing and self-contained breathing apparatus.

Unusual Fire And Explosion Hazards: Intense heat may cause nearby containers to erupt due to hazardous polymerization.

Section VI - Accidental Release Measures

Procedure For Cleanup: Ventilate area. Eliminate sources of ignition. Use self contained breathing apparatus and chemically protective clothing. Wear suitable protective clothing, gloves and eye/face protection. Absorb spill with an absorbent material such as sawdust, vermiculite or sand and place in a closed chemical container. If large spill, dike the area to prevent this material from entering water systems or sewers. Prevent contamination of soil and water. Dispose of material in accordance with federal, state/provincial and local regulations.

MATERIAL SAFETY DATA SHEET

Company Name: Superior Stone Products, Inc.
Product Name: Superior Acry-Tyte (Various Colors)
Issue Date: 5/16/08
Revision Date: 12/3/08
MSDS Number: SUP-15500

Section VII - Handling and Storage

General Procedures: Read and observe all precautions on product label and material safety data sheet before handling. Refer to product label or manufactures technical bulletins for the proper use and handling of this material. Avoid contact with skin, eyes and clothing. Do not use or store near flame, sparks or hot surfaces. Use only in well ventilated area. Keep container closed tightly and store in a cool, dry, well ventilated area. Do not weld, heat or drill container.

Storage Temperature: 50° - 100° F

Shelf Life: One (1) year when stored at room temperature.

Section VIII - Exposure Controls/Personal Protection

Respiratory Protection: When exposures can not be reduced below the PEL, respiratory protection may be required. Use only a NIOSH/MSHA approved respiratory protection if exposed to vapors above the PEL.

Ventilation: If the PEL is exceed, provide explosion proof ventilation to reduce these levels.

Protective Gloves: Wear appropriate protective gloves and clothing to prevent skin contact.

Eye Protection: Wear safety glasses, face shield or chemical goggles when handling this material.

Section IX – Physical and Chemical Properties

Part 1

Form: Paste Like

Appearance: Opaque

Odor: Characteristic strong and acrid odor

Boiling Point: >100°C (>212°F) (estimated)

Vapor Pressure: <28.00 mmHg @ 70°F (20°C)

Vapor Density: ~3.5 (water = 1)

Solubility in Water: Slightly Soluble

VOC Content: 504 - 687 g/L (estimated)

Part 2

Form: Paste Like

Appearance: Opaque

Odor: Characteristic

Boiling Point: >150°C (<302°F) (estimated)

Vapor Pressure: NA

Vapor Density: >1

Solubility in Water: Insoluable

VOC Content: Negligible

Section X - Stability and Reactivity

Stability: Stable under normal use conditions.

Hazardous Polymerization: May occur by contamination of product or depletion of inhibitor.

Incompatibility (materials to avoid): Oxidizing agents and reducing agents. Material is a strong solvent and can soften paints and rubber.

Hazardous Decomposition or Combustion Products: Heating of this product may cause irritating, acrid fumes. Hazardous gases/vapors including carbon monoxide, carbon dioxide and smoke may develop.

Section XI - Toxicological Information

Acute Oral Toxicity: No data available for this product.

Acute Dermal Toxicity: No data available for this product.

Acute Inhalation Toxicity: No data available for this product.

Section XII - Ecological Information

No data available for this product.

MATERIAL SAFETY DATA SHEET

Company Name: Superior Stone Products, Inc.
Product Name: **Superior Acry-Tyte (Various Colors)**
Issue Date: 5/16/08
Revision Date: 12/3/08
MSDS Number: SUP-15500

Section XIII - Disposal Considerations

Dispose of container and unused contents in accordance with federal, provincial, state and local requirements. For further information, contact your provincial, state or local solid waste agency or the United States Environmental Protection Agency's RCRA hotline (800-424-9346).

Section XIV - Transportation Information

United States Department of Transportation (DOT)

Shipping Name: Adhesive
Hazard Class: 3
NA/UN Number: 1133
Packing Group: II

International Maritime Organization (IMO)

Shipping Name: Adhesive
Hazard Class: 3
NA/UN Number: 1133
Packing Group: II
EmS: F-E, S-D

International Air Transport Organization (IMO)

Shipping Name: Adhesive
Hazard Class: 3
NA/UN Number: 1133
Packing Group: II
ERG Code: 3L

Please refer to U.S. DOT, IMO and IATA regulations for more information.

Section XV - Regulatory Information

Federal Regulations:

Sara Title III - Section 311

Immediate (Acute) Health Effects:	Yes
Chronic (Delayed) Health Effects:	No
Fire Hazard:	Yes
Sudden Release of Pressure Hazard:	No
Reactivity:	Yes

Sara Title III - Section 313

Methyl Methacrylate (80-62-6)
Benzoyl Peroxide (94-36-0)

Canadian Ingredient Disclosure List:

Methyl Methacrylate (80-62-6)
Triethylene Glycol Dimethacrylate Esters (109-16-0)
Benzoyl Peroxide (94-36-0)

MATERIAL SAFETY DATA SHEET

Company Name: Superior Stone Products, Inc.
Product Name: **Superior Acry-Tyte (Various Colors)**
Issue Date: 5/16/08
Revision Date: 12/3/08
MSDS Number: SUP-15500

WHMIS Classification:

Class B - Division 2

Class D - Division 2 - Subdivision B

Section XVI - Other Information

MANUFACTURER DISCLAIMER: This information is provided in good faith and is correct to the best of Superior Stone Products' knowledge as of the date hereof; however, Superior Stone Products makes no representation as to its completeness or accuracy. Customers are encouraged to make their own determination as to the suitability of this product for their purpose prior to use. Superior Stone Products disclaims responsibility to damages of any kind resulting from the use of this information. THERE ARE NO WARRANTIES OR REPRESENTATIONS, EXPRESS OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THIS INFORMATION OR TO THE PRODUCT IT DESCRIBES.