

SAFETY DATA SHEET

Company Name: Superior Stone Products, Inc.

**Product Name: Superior Epoxies E-5000 - Translucent/Colorless
- 2:1 Flowing**



Issue Date: 12/8/05

Revision Date: 8/15/18

SDS Number: 200-25110

Section I –Product and Company Identification

Product Identifier: E-5000 - Translucent/Colorless - 2:1 Flowing - Part B

Product Description/Use: Epoxy Adhesive and Filler

Product Code: 25110

Chemical Family: Amine

Company:

Superior Stone Products, Inc.

8580 Byron Commerce Drive

Byron Center, MI 49546

Phone: (616) 583-0171

24 Hour Emergency Telephone Number:

CHEMTREC 800-424-9300

GHS Hazard Classification(s):

Acute Toxicity: Category 4, Dermal

Acute Toxicity: Category 4, Oral

Serious Eye Damage/Irritation: Category 1

Reproductive Toxicity: Category 2

Specific Target Organ Toxicity - Single Exposure: Category 3

Specific Target Organ Toxicity - Repeated Exposure: Category 1

Acute Toxicity: Category 2, Inhalation

Skin Corrosion/Irritation: Category 1B

Skin Sensitization: Category 1

Chronic Aquatic Toxicity: Category 4



Symbols:

Signal Word(s): **Danger**

Hazard Statements:

H302: Harmful if swallowed.

H312: Harmful if in contact with skin.

H314: Causes severe skin burns and eye damage.

H317: May cause allergic skin reaction.

H318: Causes serious eye damage.

H330: Fatal if Inhaled

H335: May cause respiratory irritation.

H336: May cause drowsiness and dizziness.

H361: Suspected of damaging fertility or the unborn child.

H372: Causes damage to organs through prolonged or repeated exposure (central nervous system (CNS), respiratory tract, skin).

H402: Harmful to aquatic life.

Precautionary Statements:

P201: Obtain special instruction before use.

P202: Do not handle until all safety precautions have been read and understood.

P260: Do not breathe fumes/vapor.

P264: Wash skin thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P271: Use only outdoors or in a well-ventilated area.

P272: Contaminated work clothing should not be allowed out of the workplace.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P281: Use personal protective as required.

P284: Wear respiratory protection.

P301+330+331: IF SWALLOWED: rinse mouth, Do NOT induce vomiting.

SAFETY DATA SHEET

Company Name: Superior Stone Products, Inc.

**Product Name: Superior Epoxies E-5000 - Translucent/Colorless
- 2:1 Flowing**



Issue Date: 12/8/05

Revision Date: 8/15/18

SDS Number: 200-25110

P303+361+353: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+313: If exposed or concerned: Get medical advice/attention.

P310 Immediately call a POISON CENTER or doctor/physician.

P333+313: If skin irritation or rash occurs: Get medical advice/attention.

P363: Wash contaminated clothing before reuse.

P403+233 Store in a well-ventilated place. Keep container tightly closed.

P405: Store locked up.

P501: Disposal of contents/container to be specified in accordance with local/state/federal regulations.

Hazards not otherwise classified: This product contains a component that is toxic by inhalation when aerosolized or sprayed. Please refer to section 11 of the SDS for toxicity information against your intended use. If product is not being aerosolized or sprayed, the inhalation toxicity may not be applicable.

Section III – Composition/Information on Ingredients

Substance/Mixture: Mixture

<u>Ingredient</u>	<u>% (By Weight)</u>	<u>CAS#</u>	<u>EINECS No.</u>
Benzyl Alcohol	<40%	100-51-6	202-859-9
Isophorone Diamine	<40%	2855-13-2	220-666-8
Amine-Epoxy Resin Adduct	15-20%	Prop	N/A
DETA	10-15%	28063-82-3	N/A
Diethylenetriamine	<10%	111-40-0	203-865-4
Bisphenol A	<10%	80-05-7	201-245-8

Section IV – First Aid Measures

If Swallowed: Do NOT induce vomiting. Rinse mouth with water. If a person vomits when lying on their back, place them in the recovery position. Never give anything by mouth to an unconscious person. Prevent aspiration of vomit. Turn victim's head to the side. Consult a physician.

Skin Contact: Remove immediately all contaminated clothing and any extra material. Rinse skin with water. Maintain continuous irrigation until medical care can be received.

If Inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER OR doctor/physician.

Eyes: Flush with copious amounts of water, occasionally lifting the upper and lower eyelids until medical attention is received. Check for and remove any contact lenses. Seek immediate medical aid.

Section V - Fire Fighting Measures

Suitable Extinguishing Media: Alcohol resistant foam, dry chemical, carbon dioxide, dry sand, limestone powder.

Unsuitable Extinguishing Media: None known.

Special Fire Fighting Procedures: Promptly isolate scene by moving all persons from the vicinity of the incident if there is a fire. Firefighters and others exposed to vapors or products of combustion should wear self-contained breathing apparatus and full protective clothing. Equipment should be thoroughly decontaminated after use.

Hazardous Products of Combustion: May generate ammonia gas. May generate toxic nitrogen oxide gases. Burning produces noxious and toxic fumes. Downwind personnel must be evacuated.

Section VI - Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures

SAFETY DATA SHEET

Company Name: Superior Stone Products, Inc.

**Product Name: Superior Epoxies E-5000 - Translucent/Colorless
- 2:1 Flowing**



Issue Date: 12/8/05

Revision Date: 8/15/18

SDS Number: 200-25110

For Non-Emergency Personnel: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Do not touch or walk through spilled material. Provide adequate ventilation.

For Emergency Responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. See also the information for non-emergency personnel.

Methods and Materials for Containment and Cleaning Up

Small Spill: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large Spill: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section VII - Handling and Storage

Precautions for Safe Handling

Protective Measures: Put on appropriate personal protection equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not breath vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined space unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible materials, kept tightly closed when not in use. Store and use away from heat, sparks open flame or any other ignition source. Empty containers retain product residue and can be hazardous. Do no reuse container.

Advice on General Occupational Health: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for Safe Storage, Including and Incompatibles: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Segregate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do no store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Refer to the product label and/or technical data sheet for further information. Do not store in temperatures greater than 100°F.

Shelf Life: One (1) year when stored at room temperatures.

Section VIII - Exposure Controls/Personal Protection

Likely Routes of Exposure: Inhalation, Dermal, Ingestion.

Control Parameters

Occupational Exposure Limits:

<u>Ingredient Name</u>	<u>Exposure Limits</u>
Diethylenetriamine	ACGIH TLV (United States) TWA: 1 ppm
	OSHA Construction Industry PEL (United States) TWA: 10 ppm (42 mg/m ³)

SAFETY DATA SHEET

Company Name: Superior Stone Products, Inc.

**Product Name: Superior Epoxies E-5000 - Translucent/Colorless
- 2:1 Flowing**

Issue Date: 12/8/05

Revision Date: 8/15/18

SDS Number: 200-25110



NIOSH REL (United States, 10/2013)

TWA: 1 ppm (4.2 mg/m³)

Benzyl Alcohol

AIHA WEEL (2011)

TWA: 10 ppm

Engineering Controls: Use only with adequate ventilation to keep the airborne concentrations of this material below the recommended exposure standard. Engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental Exposure Controls: Emissions from ventilation of work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. .

Individual Protection Measures

Hygiene Measures: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/Face Protection: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gasses or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Hand Protection: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body Protection: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other Skin Protection: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory Protection: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section IX – Physical and Chemical Properties

Physical State: Viscous Liquid

Color: Clear to yellow/amber (darkens with age)

Odor: Fishy

Odor Threshold: Not Available

pH: Alkaline

Melting Point: Not Available

Boiling Point: >500°F/>260°C

Flash Point: 280°F/138°C

Burning Time: Not Available

Burning Rate: Not Available

Evaporation Rate: Not Available

Flammability (solid, gas): Not Applicable

SAFETY DATA SHEET

Company Name: Superior Stone Products, Inc.

**Product Name: Superior Epoxies E-5000 - Translucent/Colorless
- 2:1 Flowing**

Issue Date: 12/8/05

Revision Date: 8/15/18

SDS Number: 200-25110



Lower and Upper Explosive (Flammable) Limits: Not Applicable

Vapor Pressure: <0.01 mmHg at @ 70°F/21°C

Relative Vapor Density: Not Available (Air = 1)

Relative Density: 1.07 (Water = 1)

Solubility: Completely soluble

Partition Coefficient: n-Octanol/water : Not Available.

Auto-Ignition temperature: Not Available

Decomposition Temperature: Not Available

SADT: Not Available

Viscosity: Not Available

Section X - Stability and Reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical Stability: Material is stable at normal temperature and pressure.

Conditions to avoid: No data available.

Incompatibility (materials to avoid): Reactive Metals (e.g. sodium, calcium, zinc etc.) Materials reactive with hydroxyl compounds. Nitrous acid and other nitrosating agents. Organic acids (i.e. acetic acid, citric acid etc.). CAUTION: N-Nitrosamines many of which are known to be potent carcinogens, may be formed when the product comes in contact with nitrous, acid, nitrites or atmospheres with high nitrous oxide concentrations. Reaction with peroxides may result in violent decomposition of peroxide possible creating an explosion. Oxidizing agents.

Hazardous Decomposition: Nitric acid, ammonia, nitrogen oxides (NOx) Carbon monoxide, carbon dioxide, aldehydes, flammable hydrocarbon fragments. Nitrogen oxide can react with water vapors to form corrosive nitric acid.

Section XI - Toxicological Information

Acute Toxicity:

<u>Product/Ingredient Name</u>	<u>Result</u>	<u>Species</u>	<u>Dose</u>	<u>Exposure</u>
Product Components	LD50 - Oral (estimated)	Rat	>2,000 mg/kg	-
	LD50 - Dermal (estimated)	Rabbit	>2,000 mg/kg	-
Diethylenetriamine	LC50 (4 hr) Inhalation	Rat	>0.07-<0.3 mg/l	-

Irritation/Corrosion: Sever skin and eye irritation.

Sensitization: May cause sensitization by skin contact.

Mutagenicity: Not available

Carcinogenicity: Not available

Reproductive Toxicity: Not available

Teratogenicity: Not available

Specific Target Organ Toxicity (Single Exposure):

<u>Product/Ingredient Name</u>	<u>Category</u>	<u>Route of Exposure</u>	<u>Target Organs</u>
Benzyl Alcohol	Category 3		Respiratory tract irritation Narcotic effects
Isophorone Diamine	Category 3		Respiratory tract irritation
Amine-Epoxy Resin Adduct	Category 3		Respiratory tract irritation

Specific Target Organ Toxicity (Repeated Exposure):

<u>Product/Ingredient Name</u>	<u>Category</u>	<u>Route of Exposure</u>	<u>Target Organs</u>
Benzyl Alcohol	Category 1		Central Nervous System (SNS)

SAFETY DATA SHEET

Company Name: Superior Stone Products, Inc.

**Product Name: Superior Epoxies E-5000 - Translucent/Colorless
- 2:1 Flowing**



Issue Date: 12/8/05

Revision Date: 8/15/18

SDS Number: 200-25110

Amine-Epoxy Resin
Adduct

Category 1

Skin
Respiratory tract irritation

Aspiration Hazard: Not available

Likely Routes of Exposure: Dermal, Ingestion.

Potential Acute Health Effects:

Eye Contact: Causes serious eye damage.

Inhalation: Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness. May cause respiratory irritation. May cause allergy or asthma symptom or breathing difficulties if inhaled. Exposure to decomposition products may cause a health hazard.

Skin Contact: Causes severe burns. Harmful in contact with skin. May cause an allergic skin reaction.

Ingestion: Harmful if swallowed. Can cause central nervous system (CNS) depression. May cause burns to mouth, throat and stomach.

Symptoms Related to the Physical, Chemical and Toxicological Characteristics:

Eye Contact: Adverse symptoms may include the following: pain, watering redness.

Inhalation: Adverse symptoms may include the following: respiratory tract irritation, coughing, wheezing and breathing difficulties, asthma, nausea or vomiting, headache, drowsiness/vertigo, unconsciousness.

Skin Contact: Adverse symptoms may include the following: pain or irritation, redness, blistering may occur.

Ingestion: Adverse symptoms may include the following: stomach pains.

Delayed and Immediate Effects and also Chronic Effects from Short and Long Term Exposures:

Short Term Exposures:

Potential Immediate Effects: Not available.

Potential Delayed Effects: Not available.

Long Term Exposures:

Potential Immediate Effects: Not available.

Potential Delayed Effects: Not available.

Potential Chronic Health Effects: Not Available.

General: Causes damage to organs through prolonged or repeated exposure: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity: No known significant effects or critical hazards.

Mutagenicity: No known significant effects or critical hazards.

Teratogenicity: No known significant effects or critical hazards.

Developmental Effects: No known significant effects or critical hazards.

Fertility effects: No known significant effects or critical hazards.

Numerical Measures of Toxicity:

Acute Toxicity Estimates: Not available.

Section XII - Ecological Information

Toxicity:

<u>Product/Ingredient Name</u>	<u>Result</u>	<u>Species</u>	<u>Exposure</u>
Benzyl Alcohol	Acute LC50 - 10,000 µg/l	Fish - Blue Gill	96 hour

Persistence and Degradability: Not Available

Bioaccumulative Potential:

<u>Product/Ingredient Name</u>	<u>LogPow</u>	<u>BCF</u>	<u>Potential</u>
Benzyl Alcohol	1.1	-	low

Mobility in Soil:

Soil/water Partition Coefficient (Koc): Not available

Other Adverse Effects: No known significant effects or critical hazards.

SAFETY DATA SHEET

Company Name: Superior Stone Products, Inc.

**Product Name: Superior Epoxies E-5000 - Translucent/Colorless
- 2:1 Flowing**

Issue Date: 12/8/05

Revision Date: 8/15/18

SDS Number: 200-25110



Section XIII - Disposal Considerations

The information in this section contains generic advice and guidance. The list of identified uses in Section 1 should be consulted for any available use-specific information.

Disposal Methods: The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. Disposal of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid disposal. Attempt to use product completely in accordance with intended use. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is no feasible.

Special Precautions: This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, water ways, drains and sewers.

Section XIV - Transportation Information

DOT (DEPARTMENT OF TRANSPORTATION)

Technical Name: Amines, liquid, corrosive, N.O.S
(Isophoronediamine, Diethylenetriamine)

Hazard Class: 8

NA/UN Number: 2735

Packing Group: III

Marine Pollutant: No

Please refer to DOT regulations for more info

Canada (TDG)

Technical Name: Amines, liquid, corrosive, N.O.S
(Isophoronediamine, Diethylenetriamine)

Hazard Class: 8

NA/UN Number: 2735

Packing Group: III

Marine Pollutant: No

Please refer to TDG Regulations for more info

International Air Transport Association (IATA)

Technical Name: Amines, liquid, corrosive, N.O.S
(Isophoronediamine, Diethylenetriamine)

Hazard Class: 8

NA/UN Number: 2735

Packing Group: III

Marine Pollutant: No

ERG Code: 8L

Please refer to IATA regulations for more info.

International Maritime Organization (IMO)

Technical Name: Amines, liquid, corrosive, N.O.S
(Isophoronediamine, Diethylenetriamine)

Hazard Class: 8

NA/UN Number: 2735

Packing Group: III

Marine Pollutant: No

EmS: F-A, S-B

Please refer to IMO regulations for more info.

Special Precautions for User: Transport within users premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the products know what to do in the event of an accident or spillage.

Section XV - Regulatory Information

United States Federal Regulations:

Sara Title III - Section 311/312

<u>Criteria</u>	<u>Yes/No</u>
Immediate (Acute) Health Effects:	Yes
Chronic (Delayed) Health Effects:	No
Fire Hazard:	No
Sudden Release of Pressure Hazard:	No

SAFETY DATA SHEET

Company Name: Superior Stone Products, Inc.

**Product Name: Superior Epoxies E-5000 - Translucent/Colorless
- 2:1 Flowing**



Issue Date: 12/8/05

Revision Date: 8/15/18

SDS Number: 200-25110

Reactivity: No

State Regulations:

California Prop. 65 WARNING: This product is not known to contain any chemicals known to the State of California to cause cancer, birth defects, or any other reproductive harm.

Section XVI - Other Information


Hazardous Material Information System (United States):

Health	3
Flammability	1
Physical Hazards	0

Caution: HMIS® rating are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® rating are not required on SDSs under 29 CFR 19101200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J.J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (United States):



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325 which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

MANUFACTURER DISCLAIMER: This information is provided in good faith and is correct to the best of the manufacturers' knowledge as of the date hereof; however, the manufacturer makes no representation as to its completeness or accuracy. Customers are encouraged to make their own determination as to the suitability of this product for their purpose prior to use. The manufacturer disclaims responsibility to damages of any kind resulting from the use of this

SAFETY DATA SHEET

Company Name: Superior Stone Products, Inc.

**Product Name: Superior Epoxies E-5000 - Translucent/Colorless
- 2:1 Flowing**

Issue Date: 12/8/05

Revision Date: 8/15/18

SDS Number: 200-25110



information. THERE ARE NO WARRANTIES OR REPRESENTATIONS, EXPRESS OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THIS INFORMATION OR TO THE PRODUCT IT DESCRIBES.